

# A MODIFIED ELECTROLYSIS CELL AND A HOUSING FOR THE SAME

## BACKGROUND

5

[0001] The process for electrolyzed water is known and devices employing this process are commercially available both in portable and commercial sizes. Electrolyzed water is produced by electrolysis, a process involving the passage of an electric (D.C.) current through a mixture of potable water and brine, a solution of water and sodium chloride. The electrolysis device normally used is a cell made up of a chamber or a series of chambers with a membrane separator on each chamber.

10

15

[0002] The electrolysis cell is part of an electrolysis system for producing electrolyzed water. In the process of producing electrolyzed water, potable water is mixed with salt water or brine at a desired ratio and the resulting mixture is fed into the electrolysis cell, hereinafter also referred to simply as cell. Consequently, upon prolonged usage, electrodeposits, usually of calcium and magnesium ions are deposited and build up as scales on the electrolysis cell, thereby requiring periodic cleaning and/or replacement. While periodic cleaning can be accomplished by passage of cleaning solutions accompanied by rerouting the supply and exit lines with the use of valves, these processes merely prolong the life of the cell but has not removed the necessity of replacing the electrolysis cell. Replacement becomes necessary after a period of time because the electrodes themselves erodes and become inefficient. This invention relates

20

25

to an improvement in the design of the electrolysis cell for the production of electrolyzed water, other products of electrolysis, and on process cells involving the passage of electric current and on the housing enclosing the components of these electrolysis systems and other process systems. Current enclosed electrolysis systems such as those used for producing electrolyzed water are housed with the electrolysis cell and other components of the system in one compartment. The compartment is typically six walled with one wall or base holding most of the parts of the system and five walls or panels attaching together usually by means of screws, thereby enclosing the system. It is tedious to replace the electrolysis cell with the current housing. In a commercial unit, to replace the electrolysis cell, one has to unscrew at least one side panel of the housing adjacent to the wall attached to the cell. However, to do the replacement with less time, preferably two, a side and a top panel are removed. This facilitates access to the electrolysis cell. Once the walls are removed, one has to disconnect the cell from the compartment, the power source, system's other components and from all the tubings or pipings connected to its entry and exit ports. This replacement requires downtime which may discourage or procrastinate the replacement of the cell, thereby affecting its performance both in flow characteristics and efficiency.

**[0003]** Current electrolysis cells addressed by the claimed invention, usually have a front panel and a back panel for holding the anode and the cathode chambers. The front panel

usually has the connectors for the entrance and exit ports. The back panel may be a plain block panel or may have holes for attaching the cell to a holder to keep the cell in place. The present means for attachment is preferably by the use of self tapping screws which requires time for removal and replacement.

**[0004]** It is therefore an object of this invention to provide a housing or cabinet having a separate accessible compartment for the cell where one can immediately replace the cell without disturbing the other components of the electrolysis system.

**[0005]** It is also an object of this invention to provide different configurations of the housing or cabinet that are equally applicable for facilitating the replacement of the cell.

**[0006]** It is a further object of the invention to provide a modified electrolysis cell that allows quick methods for fastening and detaching the cell from the holder or the compartment that is enclosing the cell to reduce replacement downtime for the system.

#### BRIEF DESCRIPTION OF THE DRAWING

**[0007]** Figure 1 is an expanded view of a typical housing or cabinet for a commercial electrolysis system showing the panels that need detachment to access the electrolysis cell.

**[0008]** Figure 1A is a perspective view of a commercial electrolysis system.

**[0009]** Figure 1B is a rear view of the commercial electrolysis

system.

**[0010]** Figure 1C is a perspective view of a typical electrolysis cell.

**[0011]** Figure 2 is a perspective view of an electrolysis cell housed in a separate compartment with an optional swinging door as proposed by the invention.

**[0012]** Figure 2A is a perspective view of an electrolysis cell housed in a separate compartment with an optional sliding door.

**[0013]** Figure 2B is a perspective view of a clip-on door as alternative to a swinging or sliding door.

**[0014]** Figure 3 is a perspective view of an electrolysis cell in a platform.

**[0015]** Figure 4 is a perspective view of a screw-on platform.

**[0016]** Figure 5A and 5B are perspective views of a twist and lock platform.

**[0017]** Figure 6 shows alternate connectors for the entrance and exit ports of the electrolysis cell.

**[0018]** Figure 7 shows another design for a quick disconnect/connect electrolysis cell.

**[0019]** Figure 7A and 7B show alternate designs for the tracks or clip-ons holding the electrolysis cell.

**[0020]** Figure 8 is a perspective view of an electrolysis cell having a modified rear panel for hanging on the rear wall of the cabinet or housing.

**[0021]** Figure 9 is a perspective view of a prior art portable electrolysis system showing all the parts and its assembly.

**[0022]** Figure 10 is an exploded perspective view of the proposed portable electrolysis system.

#### SUMMARY OF THE INVENTION

5

**0023]** This invention relates to a modified electrolysis cell and a housing or cabinet for an electrolysis system. The examples and illustrations herein use the electrolysis system for producing electrolyzed water. A modified electrolysis cell  
10 generally comprises an anode chamber or a series of anode chambers and a cathode chamber or a series of cathode chambers, each chamber separated by a membrane, the chambers held together by a front panel and a rear panel having as improvement, a platform holding the electrolysis cell, the platform having a  
15 male member attached to the electrolysis cell and a matching female member connecting to the male member by a screw-on mechanism or a twist and lock mechanism. An alternative modification comprises an anode chamber or a series of anode chambers and a cathode chamber or a series of cathode chambers,  
20 each chamber separated by a membrane, the chambers held together by a front panel and a rear panel, the front panel having connectors for the entrance and exit ports, the improvement comprising an L shaped rear panel having a vertical and a horizontal member, the horizontal member securing to a track or a  
25 clip-on on a cell holder to keep the cell in place. Instead of an L shaped rear panel, the rear panel can be designed to have a

hook on one end and an inverted L on the other end for attachment by slipping into receiving brackets on a cell holder or on a wall of a compartment enclosing the electrolysis cell.

**[0024]** A commercial housing for the electrolysis cell

5 comprises a main compartment enclosing components of an electrolysis system except an electrolysis cell, the main component having six walls, a top wall, a bottom wall and four side panels; an optional second compartment enclosing a power source; an isolated third compartment enclosing the electrolysis  
10 cell separated from the main and second compartment by a wall, the isolated third compartment having at least five walls, a top wall, a bottom wall, three side panels, an open side for easily reaching to and grasping on the electrolysis cell, the open side having an optional door to open or close the second compartment;  
15 means for communicating the electrolysis cell to the components of the electrolysis system; and, means for attaching the electrolysis cell to the isolated third compartment.

**[0025]** A portable housing for an electrolysis system usually used in the home for drinking water comprises a main compartment  
20 having a front panel and a back panel enclosing components of an electrolysis system except an electrolysis cell; a second compartment enclosing a filter member; a third compartment enclosing the electrolysis cell separated from the main and second compartment, the third compartment having an optional  
25 door; means for communicating the electrolysis cell to the components of the electrolysis system; and, means for attaching

the electrolysis cell to the third compartment.

#### DETAILED DESCRIPTION OF THE INVENTION

5     **[0026]**     This invention relates to a modified electrolysis cell and a housing or cabinet for an electrolysis system. However, the teachings of this invention, although illustrated for the production of electrolyzed water, equally applies to other electrolysis cells used for producing other products of  
10     electrolysis and for process cells involving the passage of electric current through the cell so long as these require periodic replacements from the rest of the system components. A process for producing electrolyzed water employs an electrolysis cell by applying a direct current through a pair of electrodes in  
15     a cell fed with tap water and saltwater. In this process, electrodeposits, mainly consisting of calcium and magnesium deposits build up in the electrolysis cell despite periodic cleaning during its operation. A typical commercial cabinet or housing **10** for the electrolysis system such as one sold by Toyo  
20     Systems USA, Inc., 18725 E. Gale, Ste. 100, City of Industry, California, is shown in Fig. 1. The same source sells the electrolysis system and also sells the electrolysis cell as a stand alone unit. As shown, the electrolysis cell **11** along with the valves **12**, tubings **13**, electrical connectors **14**, brine pump  
25     **15**, mixing chambers **16**, power source and other accessories referred to simply herein as components of the electrolysis

system, are all confined in a single main compartment **17** which is usually enclosed by six walls or panels, **18, 19, 20, 21, 22,** and **23**. The housing or cabinet is usually made of metal or hard plastic. In the present system, in order to get into the electrolysis cell **11**, one has to detach or unscrew at least one side panel, the panel adjacent to the wall holding the electrolysis cell, which in Fig. 1 is identified as **18**. However, depending upon the orientation of the electrolysis cell, other panels may need to be detached or unscrewed. For ease of reaching into the electrolysis cell **11**, in the design shown in Fig. 1, opening the top panel, herein identified as **19** with a side panel **18** or **20** is preferable. In the present system, the electrolysis cell is usually attached to a wall by screws **24** as shown in Fig. 1B. To remove and replace the electrolysis cell, one has to additionally detach the cell from a wall as shown in Figs. 1A and 1B and from the tubings **13** connected to connectors **25** found on one side or panel of the electrolysis cell **11** as shown in Fig. 1A and 1C and also disconnect the electrical connectors **14** shown in Fig. 1C from the cell. Because of the tediousness and time required to replace the electrolysis cell, one usually delays its replacement by acceding to a slower flow rate resulting in lengthier times to produce electrolyzed water, which compromises the efficiency of the system.

**[0027]** The modified electrolysis cell and housing for this system are shown in Figs. 2-8. Figure 2 shows the main concept for the housing. The housing or cabinet must have a separate



compartment for the cell isolated from the different components of the electrolysis system. Figs. 3, 4, 5A, 5B, 7 and 8 show different designs for a modified electrolysis cell to allow quick connect/disconnect mechanisms thereby minimizing downtime in replacing the electrolysis cell. As shown in Fig. 2, the electrolysis cell **11** is isolated and enclosed in a separate compartment **26** distinct from the main compartment **17** which encloses the other components such as the valves **12**, tubings **13**, brine pump **15**, mixing chamber **16** and the power source if the latter is not enclosed in another separate compartment. Fig. 2 shows an optional swinging door **28** for closing and opening the compartment **26** housing the electrolysis cell. It is preferred to enclose the electrolysis cell during the operation to keep the cell from airborne contaminants such as dust, prevent tampering, and ensure safety from accidental touching of the electrical connectors **14** while electrolysis is going on. Fig 2A and 2B shows alternatives to a swinging door such as a sliding door **29** and a clip-on door **30** shown respectively. The doors are usually made of the same material as the housing. For the clip-on door, the front lateral sides of the open side **31** of compartment **26** should have a protruding hinge ( not shown ) for the clips to grasp on. This claimed housing removes the trouble of opening the panels of the main compartment to reach into the cell, a problem existing with the current cabinets or housing. To facilitate removal of the cell, the compartment **26** for the electrolysis cell **11** has openings **32** on the side **33** facing and

common with the main compartment **17** to accommodate and allow the tubings **13** from the main compartment to couple with the connectors **25** located on the entrance **34** and exit ports **35** of the electrolysis cell. This concept of having a separate isolated compartment for the electrolysis cell is applicable for both the current and the claimed modified electrolysis cells.

**[0028]** Fig. 3 shows the preferred connectors **25** for use with the claimed modified electrolysis cells. These connectors are usually attached to a front side **27** panel of the electrolysis cell. The front side **27** having the connectors are preferably placed facing the open side **31** of the compartment. The connectors **25** are preferably those that can quickly connect and disconnect such as the snap in elbow connectors **36** sold by Omega Engineering, Inc., One Omega Drive, P.O. Box 4047, Stamford, Connecticut 06907. Other typical forms of connectors that can be used are shown in Fig. 6. Examples are a quick connect fitting (Fig. 6A) from hose and fitting.com; MES - Male Elbow Swivel (Fig. 6B) from Parker Fluid Connectors, Parflex Division, Parker Hannifin Corporation, Ravenna, Ohio; and Quick Disconnect Couplings (Fig. 6C) from Omega Engineering, Inc.

**[0029]** To disconnect the electrical connectors **14** from the current electrolysis cell as shown in Fig. 1C, one has to unscrew the screws in front of a ring terminal **14a** connector before the latter can be removed. In the claimed modified cell of the claimed invention, a terminal spade **14b** connector or a quick disconnect such as that shown in **14c** is used so it can be

disconnected by simply loosening the screws or by unsnapping the connectors, respectively. These connectors are available at Radio Shack and other electronic supply stores.

**[0030]** A vital improvement of the claimed invention is to

5 provide a quick connect/disconnect means for the electrolysis cell **11** from the separate compartment **26** or from a cell holder in general. Figs. 3, 4, 5A, 5B, 7 and 8 show the different ways of achieving this. Fig. 3 shows the electrolysis cell in a platform **37**. It is preferable to construct the platform with the same  
10 material as the cell **11** which are usually made of hard plastic or metal. In this design, the cell is attached to the platform preferably by using an adhesive or a glue of the same or similar chemical composition as the plastic material making up the cell and the platform. For example, if the cell and the platform are  
15 made of polyvinyl chloride, a polyvinyl base adhesive will be used to glue the cell to the platform. If the cell is made of metal, welding the part or other conventional methods of attachments can be used. The platform **37** is made up of two members, a male **37a** and a female **37b**. Figs. 3 and 4 show a male  
20 member **37a**, the male member directly attached to the cell, connecting to a female member **37b** by means of a screw-on mechanism. On Figs. 5A and 5B, the male member **38a** connects with the female member **38b** through a twist and lock mechanism. In an example of a twist and lock mechanism shown in Figs 5A and 5B,  
25 the male member **38a** attached to the base of the cell **11** has a slot **39** matching a protrusion **40** overhanging the peripheral top

surface of the female member **38b**. To lock the cell in place, the male member drops into the female member through the slot **39** and once the male member occupies the circumferential area of the female member **38b**, the cell is twisted along with the male member, moving the slot away from the protrusion, thereby superimposing the protrusion over a flat surface of the male member to lock the cell in place. The male member **38a** may be solid or may have a hollow interior with solid surfaces or a solid top surface with an open base. Other twist and lock mechanisms following this concept and purpose will work equally well. Another way of easily removing and introducing the cell into the separate compartment **26** is to modify the rear panel **41** of the cell pressing on the end **42** opposite the front panel **27** of the cell. The rear panel is preferably made of metal. As shown in Fig. 7, the rear panel is preferably L-shaped with a vertical and a horizontal member. To attach the cell into the separate compartment, sliding tracks **43a** or clip-ons **43** are installed on the rear end of the bottom wall or base **44** of the compartment **26** or on a cell holder in general where the horizontal member **41a** of the rear panel **41** can be secured by sliding into or clipping into the tracks or clip-ons, respectively. As shown in Figs. 7A and 7B, these tracks **43a** or clip-ons **43** can be any number and may also be designed to cover the entire length of the horizontal member **41a**. A much simpler and quicker means is shown in Fig. 8. In this design, the electrolysis cell is constructed with a rear panel **45** having a hook **45a** on one end which in this illustration

is on the top end and an inverted L **45b** which in this illustration is on the bottom end, the hook **45a** preferably in a coaxial orientation as the inverted L **45b** to keep the cell from tilting. Tilting of the cell affect the outward flow of the liquids and gases produced during the process. The cell, as shown in Fig. 8 can be easily attached and detached by slipping the inverted L bottom end **45b** into a bottom receiving bracket **46a** and hooking the top end **45a** into a top receiving bracket **46b**. It is also possible to reverse the positions of the hook and the inverted L with minor adjustments that is easily derived from the example as shown. In this design, there should be a suitable clearance **47** above the top receiving bracket **46b** to accommodate the cell prior to slipping this into these brackets. Further, it is important for the hook and the inverted L to snugly fit into the receiving brackets to prevent movement of the cell during the process or usage.

**[0031]** Electrolyzed water used in the home primarily for drinking are housed in a more portable cabinet or housing and are preferably constructed with hard plastic. The current housing for these portable electrolysis system suffer from the same problem experienced with the commercial units described above. The electrolysis cell is likewise housed in a common compartment along with the other components of the electrolysis system such as the valves, tubings, hoses, flow sensors, electrical connectors, power control units, microprocessors and accessories. Because of the desire to make the system portable, the power

source, circuits and any computer devices which are usually enclosed in a separate compartment are normally also housed in the same common compartment, thereby making it even more difficult to replace the cell when its designated operational lifetime has expired. In the present system **100**, as typically exemplified by Model Nos. TYH-31, TYH-51, TYH-81, TYH-91, and TIS-702 of Toyo Systems, a separate compartment **48** typically house a filter member **49**, with the rest of the components all squeezed into a main compartment **50**. As shown in Fig. 9, even if the filter member **49** is in a separate compartment, this has to be removed from the unit before the main compartment enclosing the electrolysis cell can be opened. To remove the filter member **49**, as shown in Fig. 9, one has to disconnect the flexible electrolysis water hose **51** from the system housing **100**. To access the electrolysis cell **11a**, the cover **52** of the filter compartment **48** has to be removed. If the filter member **49** is secured by a locking ring **53**, this is first unlocked and removed before the filter member **49** can be released. The filter member base **54** has to be detached and the screws at back holding the front cover **56** has to be removed to expose the interior of the main compartment **50**. Even after the interior is exposed, further steps need to be done before the electrolysis cell can be replaced. These are, the bottom back water hoses **57** have to be disconnected, the bottom screws **58** and the top screws **59** holding the cell have to be disengaged as well as the electrical connectors **60**, the hose clamp **61**, and the screws (not shown)

securing the platform **62** holding the cell **11a**. Such steps are tedious and discourages an operator to replace the cell **11a** even if it is required to ensure optimum performance.

[0032] In the claimed invention as shown in Fig. 10, the filter member **49** is maintained in the separate compartment, hereinafter referred to as filter compartment **48**, but a third compartment **63** separate and different from the main compartment **50** and the filter compartment **48** is constructed to house the electrolysis cell following the same concept as that proposed for the commercial unit described above. This third compartment **63** referred to as cell compartment **63** may be constructed at the same side as or opposite that of the filter compartment **48**. Unlike the commercial unit, the portable unit usually has only a front panel or front side **64a** and a back panel or back side **64b** snapped together as shown in Fig. 10. However, like the commercial unit, the electrolysis cell **11a** connects with the tubings and electrical connectors from the main compartment **50** through openings **65** on a wall common to the third compartment and the main compartment. Likewise, for this portable electrolysis system, it is proposed to use the same types of connectors for quick connect/disconnect of the electrolysis cell with the rest of the components and to use the modified electrolysis cells having the different means for quickly connecting and disconnecting the cell to its holder such as the cell in a platform or the cell with modified rear panels. The screws used for the portable and commercial housings described herein are

preferably the self tapping screws.

**[0033]** While the examples above are directed to the electrolysis systems for producing electrolyzed water involving the passage of an electric current through a mixture of brine and water, an

5 electrolysis cell as used herein also includes cells employed for similar technologies involving the passage of an electric current through other types of mixtures. Consequently, the claimed invention is directed to all types of electrolysis cells and any process cells of similar design that needs periodic replacements.

10 These process cells are within the scope of this invention and are included within the term electrolysis cell and may be modified in the same manner as illustrated and housed similarly. Further, although the examples and illustrations show only one electrolysis cell, the compartment may hold more than one cell.

15 **[0034]** While the embodiment of the present invention has been described, it should be understood that various changes, modifications and adaptations may be made therein without departing from the spirit of the invention and the scope of the appended claims. Those skilled in the art will recognize that  
20 other and further variations of the values presented herein are possible. The scope of the present invention should be determined by the teachings disclosed herein, the appended claims and their legal equivalents.